

# **Sullivan**


---

# **Palatek®**

*“The Ultimate Performance Rotary Screw Air Compressor”*



ENCLOSED CDD  
MODEL SHOWN



**EXTENDED LIFE**  
*Mounted desiccant dryer  
to eliminate moisture  
and contaminants,  
-40° F Dew Point.*

- Rotary screw compressor,  
cool, clean air.
- Compact design.
- 100 percent duty cycle.
- 5-year air end warranty.

*Complete package with starter,  
air cooled oil cooler/aftercooler  
and protective devices for high  
temperature and low oil shutdown.  
In line filter.*

**COMPRESSOR & DESICCANT DRYER PACKAGE**

### STANDARD FEATURES

<b>ELECTRIC MOTOR:</b>	Nema T-Frame, C-Frame, double shaft, open drip proof squirrel cage, induction type. Contact factory for voltage availability. Direct coupling to motor for positive alignment.
<b>MOTOR STARTER:</b>	Full voltage magnetic starter with 120 volt controls, Nema 1 enclosure, circuit breaker, transformer and three phase overload protector.
<b>AIR INTAKE FILTER:</b>	Multi-stage dry type with replaceable element.
<b>CONTROLS:</b>	Full modulation, electronically controlled for smooth operation and lowest possible no load power. Auto dual control, timed stop or constant run.
<b>INSTRUMENTATION:</b>	Line pressure gauge, fluid reservoir gauge, hour meter, discharge temperature gauge, oil filter and separator element differential gauges.
<b>PROTECTIVE DEVICES:</b>	Class 20 overload relay, high temperature and overpressure shut down.
<b>COOLING SYSTEM:</b>	Air cooled with air cooler/aftercooler and factory filled with Palasyn 45 synthetic lubricoolant. Equipped with microfiber full flow oil filter.
<b>AIR DRYER:</b>	Desiccant air dryer and coalescing air filter for moisture removal, spin on replaceable cartridges and built for -40°F dew point.
<b>MOUNTING:</b>	Base mounted, no special foundation required. Optional tank, platform and accoustical enclosure available. Consult factory for dimensions and weights for optional equipment.

### GENERAL SPECIFICATIONS

MODEL	BASE PACKAGE	ENCLOSED PACKAGE
Lubricant Reservoir Capacity	3 Gal.	3 Gal.
Length	58"	77"
Height	35"	43"
Width	34"	38"
Weight (lbs.)	1,050	1,650
Discharge Connection	1"N.P.T.	1"N.P.T.

Sold and Serviced By:



Av. Las Trojes #109 Col. Centro Bodegero Las Trojes  
C.P. 37227  
León Guanajuato.  
Tel y Fax: +52 (477) 764 017 4 / (477) 764 017 3 / (477) 763 046 0

### CDD 15-30 HP



TANK MOUNTED OPEN CDD MODEL SHOWN.